

NON-SHUTOFF PULSE TOOLS

Performance:

Torque: 2 ft lb (2 Nm) - 369 ft lb (500 Nm)

Speed: 3000 rpm - 6800 rpm

Bolt Size: 5/16" - 3/4" (M8 - M20)

Features:

Reversible

Pistol Grip, Inline and Right Angle

Rotatable Exhaust (Pistol Grip Models)

Molded Comfort Grip (Pistol Grip Models))



FUJI Model Number	SIOUX Model Number	Rec. Bolt Size ¹		Torque Range		Drive Size ²		Free Speed rpm	Side To Center		Length		Weight		Air Consum.		Hose Size		
		in.	mm	ft lb	Nm	in.	mm		in.	mm	in.	mm	lb	kg	cfm	l/s	in.	mm	
Pistol Grip																			
FPW-110D-1		5/16	M6	5-10	7-14	3/8	10	4500	0.7	18	5.6	143	1.8	0.8	6	3	1/4	6.0	
FPW-110-1		5/16	M6	5-9	7-12	1/4	6	4500	0.7	18	5.6	143	1.8	0.8	6	3	1/4	6.0	
FPW-330D-1		5/16	M8	9-20	13-27	1/4	6	5600	0.9	23	5.9	150	2.1	1.0	14	7	1/4	6.0	
FPW-330-1		5/16	M8	13-20	18-27	3/8	10	5600	0.9	23	5.9	150	2.1	1.0	14	7	1/4	6.0	
FPW-440D-3	SPW-440D-3	5/16	M8	13-22	18-29	1/4	6	6800	0.9	23	5.9	150	2.1	1.0	14	7	1/4	6.0	
FPW-550D-3	SPW-550D-3	3/8	M8	15-25	20-34	1/4	6	6100	0.9	23	5.9	150	2.1	1.0	14	7	1/4	6.0	
FPW-660D-4 ³	SPW-660D-4 ³	3/8	M8	19-28	25-37	1/4	6	6400	0.9	23	6.4	163	2.2	1.0	18	8	3/8	10.0	
FPW-440-3	SPW-440-3	3/8	M8	19-28	25-37	3/8	10	6800	0.9	23	5.9	150	2.1	1.0	14	7	1/4	6.0	
FPW-550-3	SPW-550-3	3/8	M8	20-33	27-44	3/8	10	6100	0.9	23	5.9	150	2.1	1.0	14	7	1/4	6.0	
FPW-770D-3	SPW-770D-3	7/16	M8	25-35	34-47	1/4	6	6300	1.0	25	6.8	173	3.2	1.5	18	8	3/8	10.0	
FPW-660-4	SPW-660-4	7/16	M8	25-40	34-54	3/8	10	6400	0.9	23	6.4	163	2.2	1.0	18	8	3/8	10.0	
FPW-770-3	SPW-770-3	1/2	M8	33-57	44-76	3/8	10	6300	1.0	25	6.9	175	3.2	1.5	16	7	3/8	10.0	
FPW-880-4	SPW-880-4	1/2	M10	37-70	49-93	1/2	13	5500	1.0	25	7.5	191	3.9	1.8	19	9	3/8	10.0	
FPW-990-3	SPW-990-3	9/16	M10	48-85	64-113	1/2	13	4800	1.1	28	7.5	191	4.4	2.0	21	10	3/8	10.0	
FPW-1110-1	SPW-1110-1	9/16	M12	62-99	83-132	1/2	13	4800	1.2	30	7.6	193	4.9	2.2	21	10	3/8	10.0	
FPW-1330-1	SPW-1330-1	5/8	M12	95-147	127-196	1/2	13	3800	1.3	33	8.1	206	6.4	2.9	23	11	3/8	10.0	
FPW-1660-1		5/8	M12	162-220	220-300	3/4	19	3000	1.4	35	9.6	243	8.4	3.8	41	20	1/2	13.0	
Inline																			
FPW-110SD-1		1/4	M4	2-6	2-8	1/4	6	3200	0.7	18	8.6	218	1.4	0.7	6	3	1/4	6.0	
FPW-440SD-1	SPW-440SD-1	5/16	M8	11-19	15-25	1/4	6	5500	0.9	23	8.9	226	1.9	0.9	12	6	1/4	6.0	
FPW-550SD-1	SPW-550SD-1	3/8	M8	15-25	20-34	1/4	6	5700	0.9	23	8.9	226	1.9	0.9	13	6	1/4	6.0	
FPW-660SD-1	SPW-660SD-1	3/8	M8	19-28	25-37	1/4	6	5800	0.9	23	9.4	239	2.1	1.0	18	8	3/8	10.0	
FPW-110S-1		1/4	M4	2-6	2-8	3/8	10	3200	0.7	18	8.8	224	1.4	0.7	6	3	1/4	6.0	
FPW-440S-1	SPW-440S-1	3/8	M8	15-25	20-34	3/8	10	5500	0.9	23	8.9	226	1.9	0.9	12	6	1/4	6.0	
FPW-550S-1	SPW-550S-1	3/8	M8	20-33	27-44	3/8	10	5700	0.9	23	8.9	226	1.9	0.9	13	6	1/4	6.0	
FPW-660S-1	SPW-660S-1	7/16	M8	25-40	34-54	3/8	10	5800	0.9	23	9.4	239	2.1	1.0	18	8	1/4	6.0	
FPW-770S-1	SPW-770S-1	1/2	M8	33-57	44-76	3/8	10	6300	0.9	23	9.4	239	2.7	1.2	16	7	3/8	10.0	
Right Angle																			
FPW-440SC-1		5/16	M8	10-18	14-24	3/8	10	5000	0.7	18	10.0	255	2.8	1.3	14	7	1/4	6.0	
FPW-550SC-1		3/8	M8	16-27	22-37	3/8	10	5500	0.7	18	10.0	255	2.8	1.3	14	7	1/4	6.0	
FPW-660SC-1		3/8	M8	18-33	24-45	3/8	10	5500	0.7	18	10.0	255	3.1	1.4	14	7	3/8	10.0	
FPW-770SC-1	SPW-770SC-1	7/16	M8	25-37	33-50	1/4	6	6300	0.7	18	10.7	272	3.7	1.7	16	7	3/8	10.0	
D-Handle																			
FPW-2220S-1		3/4	M20	121-369	300-500	3/4	19	5000	1.8	45	13.8	350	15.7	7.0	45	21	1/2	13.0	

General:

Air Inlet Size: 1/4", 3/8" NPT
 Performance rated @ 90 psig (6.2 bar) air pressure
 Tools available with BSPT air inlet upon request

Standard Equipment:

Parts list, Safety and Instruction manual
 Adjustment Wrenches
 Comfort Grip

¹ Bolt capacities are based on suggested assembly torques applied to SAE Grade 5 and metric Class 9.8 fasteners under slightly lubricated conditions

² 1/4" drives are hex quick change, all others are square drives



³ For alternate shank style, order SPW-660D-40



SAFETY Precaution: Read and follow all safety and operating instructions.

WARNING: Face & eye protection must be worn while operating power tools, per ANSI B186.1

DRILLS
 ASSEMBLY
 ABRASIVE
 FINISHING
 PERCUSSIVE
 SPECIALTY
 ACCESSORIES