

“D” HANDLE DRILLS

D-Handle Drills

Performance:

Power: 1.0 hp (0.75 kw)
 Speed Range: 375 rpm - 2000 rpm
 Chuck Capacity: 3/8" (10 mm) - 1/2" (13 mm)

Features:

Non-reversible
 Trigger Start
 Side Exhaust
 Swivel Air Inlet



1465

Model Number	Chuck Capacity		Free Speed	Weight		Length		Side To Center		Air Consumption		Sound Level	Spindle Thread
	in.	mm	rpm	lb	kg	in.	mm	in.	mm	cfm	l/s	dB(A)	
"D" Handle - 1.0 hp (0.75 kw) - Non-reversible													
1465	3/8	10	1000	6.6	3.0	13.3	338	1.0	25	30	14	76	1/2"-20
▶ 1464	1/2	13	2000	6.6	3.0	13.4	340	1.0	25	30	14	76	1/2"-20
▶ 1465-1/2	1/2	13	1000	6.6	3.0	13.4	340	1.0	25	30	14	76	1/2"-20
▶ 1466	1/2	13	550	6.6	3.0	13.4	340	1.0	25	30	14	76	1/2"-20
▶ 1467	1/2	13	375	6.6	3.0	13.4	340	1.0	25	30	14	76	1/2"-20

General:

Air Inlet Size: 1/4" NPT
 Recommended Hose Size: 3/8" (10 mm)
 Performance rated @ 90 psig (6.2 bar) air pressure
 Tools available with BSPT air inlet upon request

Standard Equipment:

3-jaw Chuck & Key
 Parts list, Safety and Instruction manual
 Swivel Air Inlet

Accessories:

Drill Accessories, see pages 24-28

▶ The quick ship icon indicates our most popular models, selected for their "off-the-shelf" availability from a Sioux Authorized Distributor or distribution warehouse. See page 9 for more information on Quick Ship.

SAFETY Precaution: Read and follow all safety and operating instructions.

WARNING: Face & eye protection must be worn while operating power tools, per ANSI B186.1

