

Z-HANDLE DRILLS

Performance:

Power: 0.33 hp (0.25 kw) - 0.50 hp (0.37 kw)
 Speed Range: 1000 rpm - 5000 rpm
 Chuck Capacity: 1/4" (6 mm) - 3/8" (10 mm)

Features:

Reversible & Non-reversible
 Lever Start
 360° Rotatable Exhaust
 Suspension Bail



Model Number	Chuck Capacity		Free Speed rpm	Weight		Length		Side To Center		Air Consumption		Sound Level dB(A)	Spindle Thread
	in.	mm		lb	kg	in.	mm	in.	mm	cfm	l/s		
Non-reversible - 0.50 hp (0.37 kw)													
2S1510	1/4	6	5000	2.6	1.2	3.5	89	1.0	25	18	8	75	3/8"-24
2S1410	1/4	6	3200	2.6	1.2	3.5	89	1.0	25	18	8	75	3/8"-24
2S1310	1/4	6	2200	2.6	1.2	3.5	89	1.0	25	18	8	75	3/8"-24
2S1210	1/4	6	1600	2.6	1.2	3.5	89	1.0	25	18	8	75	3/8"-24
2S1110	1/4	6	1000	2.6	1.2	3.5	89	1.0	25	18	8	75	3/8"-24
2S1330	3/8	10	2200	2.7	1.2	3.8	97	1.0	25	18	8	75	3/8"-24
2S1230	3/8	10	1600	2.6	1.2	3.5	89	1.0	25	18	8	75	3/8"-24
2S1130	3/8	10	1000	2.6	1.2	3.5	89	1.0	25	18	8	75	3/8"-24
Reversible - 0.33 hp (0.25 kw)													
2S2410	1/4	6	3200	2.6	1.2	3.5	89	1.0	25	16	8	75	3/8"-24
▶ 2S2310	1/4	6	2200	2.6	1.2	3.5	89	1.0	25	16	8	75	3/8"-24
2S2210	1/4	6	1600	2.6	1.2	3.5	89	1.0	25	16	8	75	3/8"-24
2S2110	1/4	6	1000	2.6	1.2	3.5	89	1.0	25	16	8	75	3/8"-24
2S2330	3/8	10	2200	2.7	1.2	3.8	97	1.0	25	16	8	75	3/8"-24
2S2230	3/8	10	1600	2.7	1.2	3.8	97	1.0	25	16	8	75	3/8"-24
2S2130	3/8	10	1000	2.7	1.2	3.8	97	1.0	25	16	8	75	3/8"-24

General:

Air Inlet Size: 1/4" NPT
 Recommended Hose Size: 3/8" (10 mm)
 Performance rated @ 90 psig (6.2 bar) air pressure
 Tools available with BSPT air inlet upon request

Standard Equipment:

Parts list, Safety and Instruction manual
 3-jaw Chuck & Key
 Suspension Bail

Accessories:

Drill Accessories, see pages 24-28

▶ The quick ship icon indicates our most popular models, selected for their "off-the-shelf" availability from a Sioux Authorized Distributor or distribution warehouse. See page 9 for more information on Quick Ship.

