

**CORDED DRILLS AND DRILL/DRIVER**

**Performance:**

Voltage: 120 volts

Speed Range: 0 - 2500 rpm

Chuck Capacity: 3/8" (10 mm) - 1/2" (13 mm)

**Features:**

Reversible

Lever Start

Trigger Start (8800ES)

Variable Speed

Double Insulated



DRILLS

ASSEMBLY

ABRASIVE

FINISHING

PERCUSSIVE

SPECIALTY

ACCESSORIES

Model Number	Chuck Capacity		Maximum Free Speed rpm	Weight		Side To Center		Length	
	in.	mm		lb	kg	in.	mm	in.	mm
<b>Drill - 0.4 hp (0.3 kw)</b>									
8005ES	3/8	10	2500	3.1	1.4	1.0	25	10	254
▶ 8000ES	3/8	10	1300	3.1	1.4	1.0	25	10	254
▶ 8050ES	1/2	13	750	3.1	1.4	1.0	25	10	254
8800ES	3/8	10	1500	3.4	1.5	1.0	25	10	254
<b>Drill/Driver - 0.4 hp (0.3 kw) Keyless Chuck</b>									
▶ 8030ES	1/2	13	1300	3.6	1.6	1.0	25	10	254

**General:**

Voltage: 120 volts/3.5 amps

**Standard Equipment:**

Parts list, Safety and Instruction manual

3-jaw Chuck & Key (8005ES, 8000ES, 8050ES, 8800ES)

Keyless Chuck (8030ES)

8 ft Power Cord

**Accessories:**

Drill Accessories, see pages 24-28

▶ The quick ship icon indicates our most popular models, selected for their "off-the-shelf" availability from a Sioux Authorized Distributor or distribution warehouse. See page 9 for more information on Quick Ship.



SAFETY Precaution: Read and follow all safety and operating instructions.

**WARNING:** Face & eye protection must be worn while operating power tools, per ANSI B186.1

