

PISTOL GRIP DRILLS

Performance:

Power: 0.20 hp (0.15 kw) - 0.80 hp (0.60 kw)

Speed Range: 300 rpm - 4000 rpm

Chuck Capacity: 1/4" (6 mm) - 1/2" (13 mm)

Features:

Reversible

Trigger Start

Rapid Reverse

Comfort Grip



1410R



1455ESBR



Model Number	Chuck Capacity		Free Speed rpm	Weight		Length		Side To Center		Air Consumption		Sound Level dB(A)	Spindle Thread
	in.	mm		lb	kg	in.	mm	in.	mm	cfm	l/s		
0.20 hp (0.15 kw) - Reversible													
1412R	1/4	6	2600	1.3	0.6	6.3	160	0.6	15	10	5	75	3/8"-24
▶ 1410R	1/4	6	2000	1.3	0.6	6.3	160	0.6	15	10	5	75	3/8"-24
0.50 hp (0.37 kw) - Reversible													
1451ESBR	1/2	13	1200	3.5	1.6	9.2	234	0.9	23	25	12	78	3/8"-24
0.60 hp (0.45 kw) - Reversible													
1456ESR	1/4	6	4000	2.6	1.2	7.5	191	0.8	20	25	12	78	3/8"-24
1452ESR	1/4	6	2400	2.6	1.2	7.5	191	0.8	20	25	12	78	3/8"-24
▶ 1450ESR	1/4	6	2000	2.6	1.2	7.5	191	0.8	20	25	12	78	3/8"-24
▶ 1452ESR3/8	3/8	10	2400	2.9	1.3	7.5	191	0.8	20	25	12	78	3/8"-24
▶ 1454ESR	3/8	10	2000	2.9	1.3	7.5	191	0.8	20	25	12	78	3/8"-24
▶ 1451ESR	3/8	10	1200	3.2	1.5	8.7	221	0.9	23	25	12	78	3/8"-24
▶ 1455ESR	3/8	10	700	3.2	1.5	8.7	221	0.9	23	25	12	78	3/8"-24
▶ 1449ESR	3/8	10	450	3.2	1.5	8.7	221	0.9	23	25	12	78	3/8"-24
1455ESBR ¹	1/2	13	700	3.5	1.6	9.2	234	0.9	23	25	12	78	3/8"-24
1449ESBR ¹	1/2	13	450	3.5	1.6	9.2	234	0.9	23	25	12	78	1/2"-20
0.80 hp (0.60 kw) - Reversible													
3P2630	3/8	10	2250	5.0	2.3	8-13/16	224	1-1/32	26	33	15	81	1/2"-20
3P2530	3/8	10	1800	5.0	2.3	8-13/16	224	1-1/32	26	33	15	81	1/2"-20
3P2430	3/8	10	1200	5.0	2.3	8-13/16	224	1-1/32	26	33	15	81	1/2"-20
3P2630	3/8	10	2250	4.3	2.0	7-1/2	190	1-1/32	26	33	15	81	1/2"-20
3P2640	1/2	13	2250	4.3	2.0	7-1/2	190	1-1/32	26	33	15	81	1/2"-20
3P2340	1/2	13	850	5.0	2.3	8-13/16	224	1-1/32	26	33	15	81	1/2"-20
3P2240	1/2	13	550	5.0	2.3	8-13/16	224	1-1/32	26	33	15	81	1/2"-20
3P2140	1/2	13	300	5.0	2.3	8-13/16	224	1-1/32	26	33	15	81	1/2"-20

General:

Air Inlet Size: 1/4" NPT

Recommended Hose Size: 1/4" (6 mm) (1400 series); 3/8" (10 mm) (1450 series)

Performance rated @ 90 psig (6.2 bar) air pressure

Tools available with BSPT air inlet upon request

Standard Equipment:

Parts list, Safety and Instruction manual

3-jaw Chuck & Key

Comfort Grip

Accessories:

Drill Accessories, see pages 24-28

▶ The quick ship icon indicates our most popular models, selected for their "off-the-shelf" availability from a Sioux Authorized Distributor or distribution warehouse. See page 9 for more information on Quick Ship.

¹Support handle included



SAFETY Precaution: Read and follow all safety and operating instructions.
WARNING: Face & eye protection must be worn while operating power tools, per ANSI B186.1

