

MINIATURE ANGLE DRILLS

Performance:

Power: 0.33 hp (0.25 kw)

Speed: 800 rpm - 4300 rpm

Features:

Non-reversible

Lever Start

Rear Exhaust

90° Miniature Angle Heads



1AM1451



Model Number	Free Speed	Weight		Length		Side To Center		Air Consumption		Sound Level
	rpm	lb	kg	in.	mm	in.	mm	cfm	l/s	dB(A)
90° Angle Head - 0.33 hp (0.25 kw) - 1/4"-28 Internal Thread Spindle										
1AM1711	4300	1.5	0.7	9.7	246	0.3	8	12	6	75
1AM1611	3400	1.5	0.7	9.7	246	0.3	8	12	6	75
1AM1511	2800	1.5	0.7	9.7	246	0.3	8	12	6	75
1AM1411	2200	1.5	0.7	9.7	246	0.3	8	12	6	75
1AM1211	1100	1.7	0.7	10.7	272	0.3	8	12	6	75
1AM1111	800	1.7	0.7	10.7	272	0.3	8	12	6	75

General:

Air Inlet Size: 1/4" NPT

Recommended Hose Size: 1/4" (6 mm);

Performance rated @ 90 psig (6.2 bar) air pressure

Tools available with BSPT air inlet upon request

Standard Equipment:

Parts list, Safety and Instruction manual

Comfort Grip

Accessories:

Drill Accessories, see pages 24-28



WARNING: Face & eye protection must be worn while operating power tools, per ANSI B186.1

