

POSITIVE CLUTCH PISTOL GRIP SCREWDRIVERS

Performance:

Torque: 15 in. lb (1.7 Nm) - 300 in. lb (34.0 Nm)

Speed: 400 rpm - 3100 rpm

Features:

Reversible and Non-reversible

Trigger Start

Trigger or Rapid Reverse

Comfort Grip (1OM, SD9 series)

Rotatable Exhaust (1OM, 2P series)



2P2603



1OM2403



SD9APB-20LQ



Model Number		Maximum Torque ¹ (Soft Joint)		Free Speed	Weight		Length		Side To Center		Sound Level	
1/4" Quick Change	1/4" Internal Hex	in. lb	Nm	rpm	lb	kg	in.	mm	in.	mm	dB(A)	
1 Series - Rapid Reverse												
	1OM2603	15	1.7	3100	1.6	0.7	6.7	170	0.7	17	75	
▶	1OM2403	24	2.7	2000	1.6	0.7	6.7	170	0.7	17	75	
	1OM2303	30	3.4	1400	1.8	0.8	7.7	196	0.7	17	75	
▶	1OM2203	40	4.5	1000	1.8	0.8	7.7	196	0.7	17	75	
	1OM2103	55	6.2	725	1.8	0.8	7.7	196	0.7	17	75	
2 Series - Low Torque - Trigger Reverse												
	2P2303Q	▶ 2P2303	45	5.1	2500	2.6	1.2	6.8	173	0.9	23	82
	2P2603Q	▶ 2P2603	50	5.7	2000	2.6	1.2	6.8	173	0.9	23	82
	2P2203Q	2P2203	80	9.0	1200	3.1	1.4	8.0	203	0.9	23	82
	2P2103Q	2P2103	170	19	700	3.1	1.4	8.0	203	0.9	23	82
SD9 Series - Low Torque Clutch - Rapid Reverse												
	SD9APB-25LQ	SD9APB-25L	50	5.7	2500	2.7	1.2	8.2	208	0.9	23	78
▶	SD9APB-20LQ	▶ SD9APB-20L	65	7.3	2000	2.7	1.2	8.2	208	0.9	23	78
	SD9APB-12LQ	SD9APB-12L	100	11	1200	3.2	1.5	9.4	239	0.9	23	78
	SD9APB-7LQ	SD9APB-7L	180	20	700	3.2	1.5	9.4	239	0.9	23	78
		SD9APB-4L	300	34	400	3.2	1.5	9.4	239	0.9	23	78

General:

Air Inlet Size: 1/4" NPT

Performance rated @ 90 psig (6.2 bar) air pressure

Recommended Hose Size: 1/4" (6 mm) (1OM series);

3/8" (10 mm) (2P, SD9)

Tools available with BSPT air inlet upon request

Standard Equipment:

Parts list, Safety and Instruction manual

Comfort Grip (1OM, SD9 series)

Accessories:

Screwdriver Accessories, see page 48

Screwdriver Bits and Finders, see pages 59-60

▶ The quick ship icon indicates our most popular models, selected for their "off-the-shelf" availability from a Sioux Authorized Distributor or distribution warehouse. See page 9 for more information on Quick Ship.

¹ Torque output varies with force exerted by operator

DRILLS

ASSEMBLY

ABRASIVE

FINISHING

PERCUSSIVE

SPECIALTY

ACCESSORIES



SAFETY Precaution: Read and follow all safety and operating instructions.

WARNING: Face & eye protection must be worn while operating power tools, per ANSI B186.1



POSITIVE CLUTCH PISTOL GRIP SCREWDRIVERS

Performance:

Torque: 25 in. lb (2.8 Nm) - 300 in. lb (34.0 Nm)

Speed: 400 rpm - 4400 rpm

Features:

Reversible and Non-reversible

Trigger Start

Trigger or Rapid Reverse

Comfort Grip (SD9 series)

Rotatable Exhaust (2P series)



Model Number		Maximum Torque ³ (Soft Joint)		Free Speed	Weight		Length		Side To Center		Sound Level
1/4" Quick Change	1/4" Internal Hex	in. lb	Nm	rpm	lb	kg	in.	mm	in.	mm	dB(A)
2 Series - Mid Torque Clutch - Trigger Reverse											
▶ 2P2303AQ	▶ 2P2303A	50	5.7	2500	2.6	1.2	6.8	173	0.9	23	82
▶ 2P2603AQ	▶ 2P2603A	65	7.3	2000	2.6	1.2	6.8	173	0.9	23	82
▶ 2P2203AQ	▶ 2P2203A	100	11.3	1200	3.1	1.4	8.0	203	0.9	23	82
▶ 2P2103AQ	▶ 2P2103A	180	20	700	3.1	1.4	8.0	203	0.9	23	82
▶ 2P2503AQ		300	34	400	3.1	1.4	8.0	203	0.9	23	82
SD9 Series - Mid Torque Clutch - Rapid Reverse											
▶ SD9APB-25MQ	SD9APB-25M	50	5.7	2500	2.7	1.2	8.2	208	0.9	23	78
▶ SD9APB-20MQ	SD9APB-20M	65	7.3	2000	2.7	1.2	8.2	208	0.9	23	78
▶ SD9APB-12MQ	SD9APB-12M	100	11.3	1200	3.2	1.5	9.4	239	0.9	23	78
▶ SD9APB-7MQ	SD9APB-7M	180	20.3	700	3.2	1.5	9.4	239	0.9	23	78
▶ SD9APB-4MQ		300	34	400	3.2	1.5	9.4	239	0.9	23	78
2 Series - High Torque Clutch - Trigger Reverse											
▶ 2P2403ASQ		25	2.8	4400	2.6	1.2	6.8	173	0.9	23	82
▶ 2P2303ASQ	▶ 2P2303AS	50	5.7	2500	2.6	1.2	6.8	173	0.9	23	82
▶ 2P2603ASQ	▶ 2P2603AS	65	7.3	2000	2.6	1.2	6.8	173	0.9	23	82
▶ 2P2203ASQ		100	11	1200	3.1	1.4	8.0	203	0.9	23	82
▶ 2P2103ASQ		180	20	700	3.1	1.4	8	203	0.9	23	82
SD9 Series - High Torque Clutch - Rapid Reverse											
▶ SD9APB-25PQ	SD9APB-25P	50	5.7	2500	2.7	1.2	8.2	208	0.9	23	78
▶ SD9APB-20PQ	SD9APB-20P	65	7.3	2000	2.7	1.2	8.2	208	0.9	23	78
▶ SD9APB-12PQ		100	11	1200	3.2	1.5	9.4	239	0.9	23	78
3 Series - High Torque Clutch - Trigger Reverse											
	▶ 3P2603 ^{1,2}	84	9.5	2250	4.6	2.1	8.7	221	1.0	25	82
	▶ 3P2503 ^{1,2}	120	13	1800	4.6	2.1	8.7	221	1.0	25	82

General:

Air Inlet Size: 1/4" NPT

Performance rated @ 90 psig (6.2 bar) air pressure

Recommended Hose Size: 3/8" (10 mm) (2P, SD9, 3P series)

Tools available with BSPT air inlet upon request

Standard Equipment:

Parts list, Safety and Instruction manual

Comfort Grip (SD9 series)

Accessories:

Screwdriver Accessories, see page 48

Screwdriver Bits and Finders, see pages 59-60

▶ The quick ship icon indicates our most popular models, selected for their "off-the-shelf" availability from a Sioux Authorized Distributor or distribution warehouse. See page 9 for more information on Quick Ship.

¹ Not CE Certified

² 7/16" internal hex drive

³ Torque output varies with force exerted by operator

DRILLS

ASSEMBLY

ABRASIVE

FINISHING

PERCUSSIVE

SPECIALTY

ACCESSORIES

