

## STALL PISTOL GRIP SCREWDRIVERS

### Performance:

Torque: 18 in. lb (2.0 Nm) - 350 in. lb (39.6 Nm)

Speed: 400 rpm - 5800 rpm

### Features:

Reversible and Non-reversible

Trigger Start

Trigger or Rapid Reverse

Comfort Grip (1OM, SD9 series)

1/4" Quick Change



DRILLS

ASSEMBLY

ABRASIVE

FINISHING

PERCUSSIVE

SPECIALTY

ACCESSORIES

Model Number	Maximum Torque (Soft Joint)		Free Speed rpm	Weight		Length		Side To Center		Sound Level dB(A)
	in. lb	Nm		lb	kg	in.	mm	in.	mm	
<b>Trigger Start - Trigger Reverse</b>										
1OM2507	18	2.0	2600	1.6	0.7	6.7	170	0.7	18	75
▶ 1OM2407	24	2.7	2000	1.6	0.7	6.7	170	0.7	18	75
▶ 1OM2307	30	3.4	1400	1.8	0.8	7.7	196	0.7	18	75
▶ 1OM2207	40	4.5	1000	1.8	0.8	7.7	196	0.7	18	75
▶ 1OM2107	55	6.2	725	1.8	0.8	7.7	196	0.7	18	75
▶ 2P2407	30	3.4	4400	2.3	1.0	8.8	224	0.9	23	82
▶ 2P2307	55	6.2	2500	2.3	1.0	8.8	224	0.9	23	82
▶ 2P2607	70	7.9	2000	1.8	0.8	8.8	224	0.9	23	82
▶ 2P2207	105	11.7	1200	1.8	0.8	10	254	0.9	23	82
▶ 2P2107	185	20.9	700	1.8	0.8	10	254	0.9	23	82
▶ 2P2507	325	36.7	400	1.8	0.8	10	254	0.9	23	82
<b>Trigger Start - Rapid Reverse</b>										
▶ SD9APB-44Q	32	3.6	4400	2.4	1.1	6.4	163	0.9	23	78
▶ SD9APB-25Q	55	6.2	2500	2.4	1.1	6.4	163	0.9	23	78
▶ SD9APB-20Q	70	7.9	2000	2.4	1.1	6.4	163	0.9	23	78
▶ SD9APB-12Q	120	13.6	1200	2.9	1.3	7.6	193	0.9	23	78
▶ SD9APB-7Q	200	22.6	700	2.9	1.3	7.6	193	0.9	23	78
▶ SD9APB-4Q	350	39.6	400	2.9	1.3	7.6	193	0.9	23	78
<b>Trigger Start - Non-reversible</b>										
▶ 2P1407	40	4.5	5800	2.3	1.0	5.4	137	0.9	23	82
▶ 2P1607	90	10.2	2600	2.3	1.0	5.4	137	0.9	23	82
▶ 2P1207	140	15.8	1600	2.7	1.2	6.6	168	0.9	23	82
▶ 2P1107	240	27.1	900	2.7	1.2	6.6	168	0.9	23	82

### General:

Air Inlet Size: 1/4" NPT  
 Recommended Hose Size: 1/4" (6 mm) (1OM series); 3/8" (10 mm) (2P, SD9 series)  
 Performance rated @ 90 psig (6.2 bar) air pressure  
 Tools available with BSPT air inlet upon request

### Accessories:

Screwdriver Accessories, see page 48  
 Screwdriver Bits and Finders, see pages 59-60

### Standard Equipment:

Parts list, Safety and Instruction manual  
 Comfort Grip (1OM, SD9 series)

▶ The quick ship icon indicates our most popular models, selected for their "off-the-shelf" availability from a Sioux Authorized Distributor or distribution warehouse. See page 9 for more information on Quick Ship.



SAFETY Precaution: Read and follow all safety and operating instructions.

**WARNING:** Face & eye protection must be worn while operating power tools, per ANSI B186.1

