

TORQUE CONTROL SCREWDRIVERS

Performance:

Torque: 5.0 in. lb (0.6 Nm) - 200 in. lb (22.6 Nm)

Speed: 300 rpm - 2800 rpm

Screw size: #6 - 5/16" (M3 - M8)

Features:

Push-to-start and Lever Start

Reversible

Locking Button Reverse

External Clutch Adjustment



1ST2108



2L2108QTC



1OT2208Q



Model Number		Screw Capacity ¹		Torque Range (Soft Joint)		Free Speed	Weight		Length		Side To Center		Sound Level	
1/4" QC ²	1/4" IH ³	in.	mm	in. lb	Nm	rpm	lb	kg	in.	mm	in.	mm	dB(A)	
Inline - Push To Start														
		#6	M3	5.0-14	0.6-1.5	2800	1.4	0.6	8.3	211	0.6	15	75	
▶	1ST2308Q	1ST2308	#8	M4	5.0-25	0.6-3.0	1500	1.6	0.7	9.3	236	0.6	15	75
▶	1ST2208Q	1ST2208	#10	M4	5.0-35	0.6-4.0	1100	1.6	0.7	9.3	236	0.6	15	75
▶	1ST2108Q	1ST2108	#10	M5	5.0-50	0.6-5.5	800	1.6	0.7	9.3	236	0.6	15	75
Inline - Lever Start														
	2L2308QTC		1/4	M6	30-96	3.4-10.8	900	3.7	1.7	12.1	307	1.0	25	80
	2L2208QTC		1/4	M6	36-144	4.0-16.3	500	3.7	1.7	12.1	307	1.0	25	80
	2L2108QTC		5/16	M8	60-200	6.8-22.6	300	3.7	1.7	12.1	307	1.0	25	80
Pistol Grip - Push To Start														
▶	1OT2508Q		#6	M3	5.0-14	0.6-1.5	2600	1.9	0.9	7.8	200	0.7	17	75
	1OT2308Q		#8	M4	5.0-25	0.6-3.0	1400	2.1	1.0	8.8	225	0.7	17	75
	1OT2208Q	1OT2208	#10	M4	5.0-35	0.6-4.0	1000	2.1	1.0	8.8	225	0.7	17	75
	1OT2108Q	1OT2108	#10	M5	5.0-50	0.6-5.5	725	2.1	1.0	8.8	225	0.7	17	75

General:

Air Inlet Size: 1/4" NPT
 Recommended Hose Size: 1/4" (6 mm) (1OT, 1ST series); 3/8" (10 mm) (2L series)
 Performance rated @ 90 psig (6.2 bar) air pressure
 Tools available with BSPT air inlet upon request

Standard Equipment:

Parts list, Safety and Instruction manual
 Comfort Grip (1OT, 1ST series)
 Suspension Bail (Inline models)

Accessories:

Screwdriver Accessories, see page 48
 Screwdriver Bits and Finders, see pages 59-60

▶ The quick ship icon indicates our most popular models, selected for their "off-the-shelf" availability from a Sioux Authorized Distributor or distribution warehouse. See page 9 for more information on Quick Ship.

¹ Screw capacities are based on suggested assembly torques applied to SAE Grade 5 and metric Class 9.8 fasteners under slightly lubricated conditions

² Quick Change

³ Internal Hex



SAFETY Precaution: Read and follow all safety and operating instructions.

WARNING: Face & eye protection must be worn while operating power tools, per ANSI B186.1

DRILLS

ASSEMBLY

ABRASIVE

FINISHING

PERCUSSIVE

SPECIALTY

ACCESSORIES

