

Reversible Drills

Pistol Grip 3/8", 1/2"

Drills supplied with Jacobs Multi-Craft chucks unless otherwise requested. See pages 93-95 for other available chucks.

Light Industrial Duty

D318R 3/8" Reversible



FEATURES:

- Planetary gearing.
- Handle exhaust.
- Variable speed trigger.
- One hand reverse lever.
- Flush grease fitting in the gear head.


Model: D318R

Code: 79476

Free speed:	1,800 RPM
Chuck size:	3/8" 9.5 MM
Air inlet NPT:	1/4"
Hose size:	3/8" 9.5 MM
Avg. air cons:	4 CFM 0.11 CMM
Spindle thread:	3/8" - 24
Length:	6.1/2" 165 MM
Weight:	3 LB 1.36 KG

Heavy Duty

D320R 3/8" Reversible



With silencer

FEATURES:

- Full gear cage for heavy duty use.
- Planetary gears have needle bearings.
- Handle exhaust with silencer.
- Variable speed trigger.

Model: D320R

Code: 105686

Free speed:	2,000 RPM
Chuck size:	3/8" 9.5 MM
Air inlet NPT:	1/4"
Hose size:	3/8" 9.5 MM
Avg. air cons:	4 CFM 0.11 CMM
Spindle thread:	3/8" - 24
Length:	6.1/2" 165 MM
Weight:	2.5 LB 1.1 KG

Light Industrial Duty

D440R 1/2" Reversible.

D480R 1/2" Reversible.



FEATURES:

- Planetary gearing.
- Dead handle to absorb stall torque reaction.
- Handle exhaust.
- Variable speed trigger.
- One hand reverse lever.
- Flush grease fitting in the gear head.

Model: D440R

Code: 106762

Free speed: 400 RPM

Model: D480R

Code: 88762

Free speed: 800 RPM

Chuck size:	1/2" 12.7 MM
Air inlet NPT:	1/4"
Hose size:	3/8" 9.5 MM
Avg. air cons:	4 CFM 0.11 CMM
Spindle thread:	3/8" - 24
Length:	7" 178 MM
Weight:	3.6 LB 1.6 KG




DHA400 Dead Handle

Code: 92927

Extra Heavy Duty

D450RHD 1/2" Reversible



c/w a Wespro
10043 HD
key type chuck.

FEATURES:

- Full gear cage for heavy duty use.
- 1/2" - 20 thread spindle.
- Dead handle to absorb stall torque reaction.
- Handle exhaust.
- Variable speed trigger.
- One hand reverse lever.
- Flush grease fitting in the gear head.

Replacement chucks see pages 93-95

Model: D450RHD-10043

Code: 158864

Free speed:	500 RPM
Chuck size:	1/2" 12.7 MM
Air inlet NPT:	1/4"
Hose size:	3/8" 9.5 MM
Avg. air cons:	4 CFM 0.11 CMM
Spindle thread:	1/2" - 20
Length:	7" 178 MM
Weight:	4 LB 1.8 KG